NETWORK

# Data sheet: WL-201

| | | |
|---|---|---|
| Product code | : | WL-201 |
| Product name | : | Wireless Network Printer server |
| EAN code | : | 8716502006069 |
| Qty. masterpack / carton | : | 5/20 |
| Product weight | : | 100 gr. |
| Product dimensions | : | 95(W) x 63 (D) x 25mm (H) |
| Gift box weight | : | 1.5 kg. |
| Gift box dimensions | : | 210 (W) x 72 (D) x 147 mm (H) |
| Masterpack weight | : | 5.75 kg. |
| Masterpack dimensions | : | 340 (W) x 190 (D) x 270 mm (H) |
| Carton weight | : | 11.5 kg. |
| Carton dimensions | : | 400(W) x 350 (D) x 280mm (H) |

The Wireless Network printer server USB enables you to very simply add a printer to your network without the use of wires. This may be a completely wireless network, in which all wireless workstations share the use of the printer, or a combined network in which wireless as well as cabled workstations have access to the printer via an Access Point. Furthermore you can create a direct wireless connection between your printer and your computer (as long as it's equipped with a wireless network adapter). The Wireless Network printer server allows you to locate your printer anywhere in your home or office for flexible working.

## Box content:

- Wireless Network printer server
- USBCD-ROM (including full manual)
- Installation Guide
- Power adapter

## System requirements:

- Wireless LAN connection (802.11b/g) or RJ-45 LAN connection
- USB printer
- Windows 98SE/2000/ME/XP
- CD Rom drive

NETWORK

# Data sheet: WL-201

## Key features:

- 802.11g Wireless Station
- Data Rate up to 54Mbps
- Fully Compatible with 802.11b
- 1 x USB 2 Printer Port

## Technical specifications:

- Frequency : 2.4 to 2.4835 GHz (ISM Band)
- Security : 40 bits & 128 bits WEP, ESSID, WPA-PSK, Open/Shared system authentication
- 11 Channels (US & Canada), Channel 1~11
- 13 Channels for Pan-Europe & Australia, Channel 1~13
- 4 Channels for French, Channel 10~13
- 2 Channels for Spain, Channel 10~11
- Data Rate : 1~54Mbps
- Network Interface : Wireless: IEEE 802.11b, IEEE 802.11g; Ethernet: 10BaseT/100BaseTx
- Antenna - 2dBi Antenna
- Range Coverage
- IEEE802.11b (11Mbps): Indoor: 50m, Outdoor: 150M (depends on environment)
- IEEE802.11g (54Mbps): Indoor: 30m, Outdoor: 60m (depends on environment)
- Printer Connection : USB 2.0 (1.1 Compliant)
- Protocol Support TCP/IP, NetBEUI, AppleTalk
- Operating System Support : Windows 95/98/2000/NT/Me/XP, Macintosh (OS 9.x and higher), Unix
- Printing Methods : PTP (Peer-to-Peer) over TCP/IP or NetBEUI protocol, LPD printing, SMB printing (via NetBEUI or TCP/IP protocol), IPP (Internet Printing Protocol), AppleTalk (EtherTalk)
- Management Tools : BiAdmin (Windows Application), Web-based management (HTTP), Setup Wizard
- LEDs : 1xStatus, 1xError
- Diagnostic Button: Print current settings or Reset to factory defaults.
- Power Supply : DC 5V / 2A
- Emission : FCC, CE